



# SLC BLOCKY R62 WH 500TED 927

## IP54 24°

Blocky has a pulled-down edge of 60 mm for glare reduction and character. The light source is deeply recessed and is not visible from the side angles. This gives the impression that there is a cube with a light inside, not a downlight.



Light technic	
Product ID	3234518
Beam angle	Medium beam 21-40° °
Lamp efficacy	56 lm/W
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Rated luminous flux according to IEC 62722-2-1	500 lm
Colour of light	White
Luminous flux	500 - 500 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	56 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	9 - 9
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Covering of the luminaire with thermally insulating material possible	No
Control gear included	Yes
Fit for workplace according to EN 12464-1	No

14.01.2021

Subject to changes and printing errors

<b>Max. system power</b>	9 W
<b>Adjustability</b>	Not adjustable
<b>Rated ambient temperature according to IEC62722-2-1</b>	-10 - 45 °C
<b>Dimming phase cut-off</b>	Yes
<b>Power factor</b>	0.95
<b>Dimming method</b>	Trailing edge
<b>Input</b>	
<b>Voltage type</b>	AC/DC
<b>Nominal voltage</b>	220 - 240 V
<b>Output</b>	
<b>LED nominal current at constant current</b>	230 - 230 mA
<b>Installation</b>	
<b>Height/depth</b>	103 mm
<b>Built-in width</b>	62 mm
<b>Built-in height/depth</b>	43 mm
<b>Length</b>	70 mm
<b>Built-in length</b>	62 mm
<b>Width</b>	70 mm
<b>Outer diameter</b>	70 mm
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Plug clamp
<b>Built-in diameter</b>	62 mm
<b>Suitable for suspended mounting</b>	No
<b>Number of poles</b>	3
<b>Suitable for wall mounting</b>	No
<b>Suitable for built-in mounting</b>	Yes
<b>Connectable conductor cross section</b>	0.75 - 2.5 mm <sup>2</sup>
<b>Type of wiring</b>	Suitable for through wiring
<b>Suitable for ceiling mounting</b>	Yes
<b>logistics data</b>	
<b>Imported by</b>	The Light Group
<b>Brand</b>	SLC
<b>General data</b>	
<b>GTIN</b>	7070938054508
<b>Pallet length</b>	1200 mm
<b>M-pack length</b>	585 mm
<b>F-pack length</b>	115 mm

14.01.2021  
Subject to changes and printing errors